

## KAC-CD1300C

### Portable Professional Table-Top Chairman Unit



#### DESCRIPTION

Introducing the KAC-CWD1200 Series of digital wireless tabletop audio conference units, engineered for professional-grade performance and user-friendly plug-and-play functionality. This system offers a wide range of frequencies, ensuring outstanding sound clarity and intelligibility. Their versatility enhances communication and collaboration, making them suitable for small teams and large gatherings alike.

Each unit features a high-quality condenser gooseneck microphone, an intuitive On/Off button, and a sleek, compact design. The integrated LED display provides real-time information on selected frequency, battery status, and volume levels, making it an ideal solution for seamless and effective communication in any setting.

#### MAIN APPLICATIONS

- The KAC-CD1300 series is meticulously crafted for meeting and board rooms, where effective communication is essential.
- In corporate environments, this system promotes teamwork and efficiency, facilitating seamless presentations and strategic decision-making.

#### MAIN FEATURES

- **Priority Function**
- **Outstanding Sound Clarity**
- **Compact and Light Weight Design**
- **High Sensitivity and Intelligibility**
- **Innovative Resilient Network Design**
- **Plug and Play Operation**
- **Long Flexible Gooseneck Microphone**
- **Status LED Indicator and Talk Button**
- **Fully Expandable**

#### TECHNICAL SPECIFICATIONS

|                               |   |
|-------------------------------|---|
| Type                          | Condenser                                 |
| Effective frequency range, Hz | 40 - 16,000                               |
| Sensitivity                   | -44 dB $\pm$ 2dB                          |
| Connection                    | CAT6 Cable                                |
| Gooseneck Microphone          | 410/470 mm                                |
| Storage Temperature           | -20°C to +70°C                            |
| Operation Temperature         | 0° to +40°C                               |
| Humidity                      | 80% RH to at least +65°C (non condensing) |
| Altitude                      | 3000 Meter maximum                        |
| Approx. weight, Kgs           | 1.1                                       |
| Color / Finish                | Black                                     |



Every effort has been made to ensure that all the information in this document was correct at the time of going to press. However we are constantly striving to improve our range wherever possible and therefore reserve the right to change the specification of any product without prior notice

R&D is constantly improving our products therefore specifications, features and appearance are subjected to change without notice

## ULTRAKPA

For USA, Canada, South America, Europe, Africa & Middle East - [info@ultrakpa.com](mailto:info@ultrakpa.com)

**ULTRAKPA Inc**

Astoria, NY 11103, U.S.A

Phone +1 (914) 210-1483 [info@ultrakpa.com](mailto:info@ultrakpa.com)

[www.Ultrakpa.com](http://www.Ultrakpa.com)