KAS-4040MS Pro-Series Column Speakers



Image is Illustrative.

DESCRIPTION

ULTRAKPA offers wide selection of speakers which can be used in a variety of applications from speakers to column speakers to ceiling, horn and cabinet speakers. ULTRAKPA column speakers offer high speech intelligibility for professional applications.

This new line of column speakers are made of high quality components providing outstanding sound quality and wide horizontal coverage angle and narrow vertical coverage angle to meet the most demanding applications with efficient reliable performance.

MAIN APPLICATIONS

- Educational Applications, Universities, Lecture Rooms and Traning Centers.
- House of Worship, Churches, Medium Sized Meeting Rooms.

MAIN FEATURES

- 2-Way Speaker
- Wide Horizontal Coverage Angle
- **Significant Vocal Clarity**
- **Suitable for Indoor Professional Applications**
- **Easy Installation**
- **Remarkable Sound Quality**
- **Excellent Intelligibility**
- **Reliable Performance**

TECHNICAL SPECIFICATIONS

Speaker type	2-way
Transducer low	2 x 3.5" woofer
Rated power, watts	40
Max. power, watts	80
Effective frequency range, Hz	100-20000
S.P.L., @ 1 m, 1 Watt, 1 kHz, dB	95
S.P.L., @ Full power / 1 m, dB	111
Dispersion Angle	120° (H) x 40° (V)

Dimensions (W x H x D), mm	160 x 416 x 115
Storage Temperature	-20°C to +70°C
Operation Temperature	0°to +40°C
Humidity	80% RH to at least +65°C
Altitude	3000 Meter maximum
Approx. weight, Kgs	2.75
Color / Finish	Ivory: KAS4040MSC
	Black:KAS4040MSB







Every effort has been made to ensure that all the information in this document was correct at the time of going to press. However we are constantly striving to improve our range wherever possible and therefore reserve the right to change the specification of any product without prior notice.

R&D is constantly improving our products therefore specifications, features and appearance are subjected to change without notice

