# **KAR5105AD**

# PUBLIC ADDRESS AMPLIFIER MONITOR UNIT



The KAR5105AD is an Amplifier Monitor Unit for up to 10 power 100V amplifiers. A built in speaker with a corresponding selector switch allows the user to listen to each audio amplifier output (100V). A headphone connection (with automatic override of the speaker) is also provided.

Each input is isolated with a transformer and has an input control (1 to 100V) together with a LED meter range allowing the adjustment of each channel separately.

An additional Auxiliary input (line level) may be used to listen to a preamplifier output.

- Monitors up to 10 power amplifiers
- Monitor input level adjustable from 1-100V
- Balanced, transformer coupled inputs
- LED meter for each channel
- Available in ivory and gray colors

- Built-in speaker and headphone output
- AUX input for monitoring pre-amplifier output
- Mains voltage selectable between 120VAC, 230VAC, 240VAC and 24VDC



# **KAR5105AD**

# **TECHNICAL SPECIFICATIONS**

#### **ELECTRICAL**

Frequency Responce	Less than -3dB (100Hz - 20kHz)
T.H.D. (1kHz)	Less than 0.5%
Input Sensitivity / Impedance	1V - 100V / 10 ohm balanced
Rated Monitor	Speaker - 2W max.
	Headphone - 0.1W max.
Power Source	AC 120V / 230V / 240V,
	as indicated on the rear panel
Standby Power	24V DC
Power Consumption	All operations - 12W
•	1 Ch operation - 8.5W
Approval	CE


#### **ENVIRONMENT**

Storage Temperature	-20°C to +70°C, -4° to 158°F
Operation Temperature	0°C to +40°C, 0°F to 104°F
Humidity	80% RH to at least +65°C (non condensing) 80% RH to at least-149°F (non condensing)
Altitude	3000 meter maximum, 10,000 feet maximum

# **MECHANICAL**

Dimensions	483(W) x 88(H) x 200(D) mm 19(W) x 3.54(H) x 8(D) inches
Weight	4.7 Kg, 10.4 lbs.

#### KAR5105AD - Front



Conversion: 1" = 25.4mm
Measurement conversions are approximate
Design and specifications subject to change without notice.
For USA, Canada, South America, Europe, Africa & Middle East- info@ultrakpa.com

### **ULTRAKPA Inc:**

Astoria, NY 1103, U.S.A Phone + 1 (914) 210-1483 info@ultrakpa.com

